

# Ningbo Autowin Tools Co., Ltd.

Tire Repair String

## MATERIAL SAFETY DATA SHEET

Page 1 of 6  
February 21, 2012

### 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Name: Tire Repair String

CAS Number: Mixture

Part #:

15161TF, 15162TF  
15163TF, 15164TF  
15165TF, 15184TF  
15206TF, 15207TF  
15280TF, 15281TF  
151620138

Company Identification: Ningbo Autowin Tools Co., Ltd.

Fangxin Road, Fangqiao Ind. Zone, Fenghua, Ningbo 315514 China

Ph: 86-574-2852-5801 (For product information)

800-424-9300 or 202-483-7616 (CHEMTREC: For emergencies)

### 2. COMPOSITION / INFORMATION ON INGREDIENTS:

<u>Chemical Name</u>	<u>Amount (optional)</u>	<u>CAS Number</u>
Butyl Rubber	15.0%	N/A
Polybutadiene Rubber	15.0%	N/A
Nylon	60.0%	32131-17-2
Non Hazardous Ingredient(s)	10.0%	Proprietary

\*California Prop 65: This product does contain ingredients which are known to the state of California to cause cancer, birth defects, or other reproductive harm.

HAZARDS DISCLOSURE: This product contains NO known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200. As defined under Sara 311 and 312, this product contains known hazardous materials.

### 3. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW – WARNING! CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.**

HMIS Rating: Health - 1, Flammability - 1, Reactivity - 0, Personal Protection Index - A

NFPA Rating: Health - 1, Flammability - 1, Reactivity - 0

NFPA/HMIS Definitions: (0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme).

Protective Equipment: Safety glasses and gloves

#### Potential Health Effects

**Inhalation:** Inhalation can cause severe irritation of mucous membranes and upper respiratory tract.

Symptoms may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, dizziness and vomiting.

**Ingestion:** Causes irritation to the gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhea.

**Skin Contact:** Causes irritation to skin. Symptoms include redness, itching, and pain. Repeated or prolonged contact with the skin has a defatting effect and may cause dryness, cracking, and possibly dermatitis.

**Eye Contact:** Causes irritation, redness, and pain.

**Chronic Exposure:** Not determined

**Aggravation of Pre-existing Conditions:** Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

### 4. FIRST AID MEASURES

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion:** Give large amounts of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately. Do not induce vomiting.

**Skin Contact:** Immediately flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

## 5. FIRE FIGHTING MEASURES

**Fire:** Flash point: N/A

**Autoignition temperature:** 400C

**Flammable limits in air % by volume:** lcl: N/A; uel: N/A

**Flammable Liquid and Vapor/ Contact with strong oxidizers may cause fire.**

**Fire Extinguishing Media:** Water spray, dry chemical, alcohol foam, or carbon dioxide. Water may be ineffective. Water spray may be used to keep fire exposed containers cool.

**Special Information:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures. Vapors can flow along surfaces to distant ignition source and flash back.

## 6. ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container.

## 7. HANDLING AND STORAGE

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

**HANDLING (PERSONNEL):** Handle in accordance with good hygiene and safety procedures. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. When transferring materials ground and bond containers, use spark proof tools and explosion proof equipment. Since empty containers contain product residue, follow all hazard warnings and precautions even after container is emptied. Keep away from sources of ignition.

**STORAGE PRECAUTIONS:** Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from any source of heat or ignition. Avoid dust dispersal. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## MATERIAL SAFETY DATA SHEET

### Airborne Exposure Limits:

-ACGIH Threshold Limit Value (TLV) in ppm (TWA), A4 - Not classifiable as a human carcinogen.

Butyl Rubber	N/A
Polybutadiene Rubber	N/A
Nylon	N/A

**Ventilation System:** A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

**Personal Respirators (NIOSH Approved):** If the exposure limit is exceeded and engineering controls are not feasible, a full facepiece respirator with organic vapor cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air purifying respirators do not protect workers in oxygen-deficient atmospheres. See also 23 CFR1910.134.

**Skin Protection:** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Eye Protection:** Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Solid	COLOR: N/A
ODOR: N/A	SOLID CONTENT % (±1): 100%
SOLUBILITY IN WATER: Insoluble	VISCOSITY: N/A
SPECIFIC WEIGHT: N/A	PH: N/A
MELTING/FREEZING POINT: N/D	BOILING POINT: N/A
EVAPORATION RATE (BuAc=1): N/D	FLASH POINT: N/A
AUTOIGNITION TEMPERATURE: N/A	VAPOR DENSITY (Air=1): N/A
% VOLATILES BY VOLUME @ 21°C (70°F): N/D	VAPOR PRESSURE (mm Hg): N/D
COMBURENT PROPERTIES: No	PARTITION COEFFICIENT (n-octanol/water): N/A

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under ordinary conditions of use and storage. Heat will contribute to instability.

**Hazardous Decomposition Products:** Carbon dioxide and carbon monoxide may form when heated to decomposition.

**Hazardous Polymerization:** Will not occur.

**Incompatibilities:** Avoid heat, flame and other sources of ignition.

**Conditions to Avoid:** No information found.

## 11. TOXICOLOGICAL INFORMATION

Acute effects: stinging eyes. Symptoms may include: Contact with skin may cause slight irritation. Ingestion may cause health problems including stomach pain and sting, nausea and sickness. This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

### Cancer Lists

Ingredient	NTP Carcinogen		IARC Category
	Known	Anticipated	

## MATERIAL SAFETY DATA SHEET

BUTYL RUBBER	No	No	None
POLYBUTADIENE RUBBER	No	No	None
NYLON	No	No	None

### 12. ECOLOGICAL INFORMATION

**Environmental Toxicity:** No Information Available.

### 13. DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

### 14. TRANSPORTATION INFORMATION

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packaging or in packaging made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

#### Domestic (Land, D.O.T.)

ADR:

PRODUCT LABEL: Non Hazardous Material  
UN NUMBER: N/A  
D.O.T. HAZARD CLASS: N/A  
PACKING GROUP: N/A  
D.O.T. SHIPPING NAME: Non Hazardous Material  
PRODUCT RQ (LBS): N/A  
SPECIAL PROVISIONS: N/A

#### International (Water, I.M.O.)

IMO CLASS:

PRODUCT LABEL: Non Hazardous Material  
UN NUMBER: N/A  
D.O.T. HAZARD CLASS: N/A  
PACKING GROUP: N/A  
D.O.T. SHIPPING NAME: N/A  
PRODUCT RQ (LBS): N/A  
EMS:

#### International (Air, I.C.A.O.)

IATA:

PRODUCT LABEL: Non Hazardous Material  
UN NUMBER: N/A  
D.O.T. HAZARD CLASS: N/A  
PACKING GROUP: N/A  
D.O.T. SHIPPING NAME: N/A

## MATERIAL SAFETY DATA SHEET

### 15. REGULATORY INFORMATION

**FEDERAL REGULATORY STATUS:** OSHA Classification: Product is Non - hazardous according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Chemical Weapons Convention:** No    **TSCA 12(b):** No    **CDTA:** No

**SARA 311/312:** Acute: No    Chronic: No    Fire: No    Pressure: No

**Reactivity:** No

**Australian Hazchem Code:** None allocated.

**Poison Schedule:** None allocated.

**WHMIS:** This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA). This material or all of its components are listed on the Canadian Domestic Substances List (DSL). This material or all of its components are listed (or considered as having been notified) on the European Inventory of Existing Chemical Substances (EINECS). Other inventory lists: ENCS (Japan), Korea, Australia, China (Draft), PICCS (Philippines), Japan (ENCS).

### 16. OTHER INFORMATION

**Label Hazard Warning:** WARNING! CAUSES IRRITATION TO SKIN, AND EYES.

**Label Precautions:**

Keep container closed.

Use only with adequate ventilation. Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

**Label First Aid:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, give large amounts of water to drink. Never give anything by mouth to an unconscious person. In all cases, get medical attention.

Prepared By: Paul Eigbrett  
Approval Date: February 21, 2012

Part Number: N/A  
Supersedes Date: February 20, 2009

**ADDITIONAL INFORMATION:**

The data in this Material Safety Data Sheet relates only to the specific material designated herein. It does not relate to use in combination with any other material or in any process. This Material Safety Data Sheet (MSDS) has been reviewed to fully comply with the guidance contained in the ANSI MSDS standard (ANSI Z400.1-1998).

This information is furnished gratuitously and independent of the sales of the product without warranty, expressed or implied, except that it is accurate to the best knowledge of Ningbo Autowin Tools Co., Ltd.. NO WARRANTY, EITHER EXPRESS OR IMPLIED, WHETHER OF MERCHANTABILITY OF FITNESS OF ANY NATURE OR OTHERWISE WITH RESPECT TO THE PRODUCT OR TO THE DATA HEREIN IS MADE HEREUNDER. The data on this sheet

# Ningbo Autowin Tools Co., Ltd.

Tire Repair String

## MATERIAL SAFETY DATA SHEET

Page 6 of 6  
February 21, 2012

are related only to the specific material designated herein. Ningbo Autowin Tools Co., Ltd. assumes no legal responsibility for use or reliance upon these data. Ningbo Autowin Tools Co., Ltd. shall not be responsible for any damages directly or indirectly resulting from the publication or use of or reliance upon data contained herein. Material Safety Data Sheets are available for all Ningbo Autowin Tools Co., Ltd. products and you are urged to obtain those sheets for all those products that you buy, process, use or distribute. You may also have a legal obligation to advise anyone working with or exposed to such products of the information contained in the Material Safety Data Sheets.

END OF MSDS